

## 11000WHW WILFLEX OASIS HYDRATE WHITE

Version Number 1.5 Page 1 of 19 Revision Date 04/02/2018 Print Date 04/03/2018

# SAFETY DATA SHEET

#### 11000WHW WILFLEX OASIS HYDRATE WHITE

## **Section 1. Identification**

**GHS product identifier** : 11000WHW WILFLEX OASIS HYDRATE WHITE

Chemical name: MixtureCAS number: MixtureOther means of identification: FO20029025Product type: liquid

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications. Plastics.

Supplier's details : POLYONE CORPORATION

33587 Walker Road, Avon Lake, OH 44012

1 (440) 930-1000 or 1 (866) POLYONE

**Emergency telephone number** (with hours of operation)

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or

accident).

## Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A

#### **GHS** label elements



## 11000WHW WILFLEX OASIS HYDRATE WHITE

 Version Number 1.5
 Page 2 of 19

 Revision Date 04/02/2018
 Print Date 04/03/2018

Hazard pictograms

 $\diamondsuit$ 

Signal word : Warning

**Hazard statements** : Causes serious eye irritation.

Causes skin irritation.

**Precautionary statements** 

**General** : Not applicable.

**Prevention**: Wear protective gloves. Wear eye or face protection. Wash hands

thoroughly after handling.

**Response**: IF ON SKIN: Wash with plenty of soap and water. Take off

contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical

attention.

StorageNot applicable.DisposalNot applicable.Supplemental label elementsNone known.Hazards not otherwise classifiedNone known.

# Section 3. Composition/information on ingredients

Substance/mixture:MixtureChemical name:MixtureOther means of identification:FO20029025

### CAS number/other identifiers

Ingredient name	%	CAS number
Distillates (petroleum), hydrotreated light	10 - 25	64742-47-8
Titanium dioxide	10 - 25	13463-67-7
1,2-Propanediol	5 - 10	57-55-6



## 11000WHW WILFLEX OASIS HYDRATE WHITE

Version Number 1.5 Page 3 of 19 Revision Date 04/02/2018 Print Date 04/03/2018

Urea	3 - 5	57-13-6
Paraffin waxes and Hydrocarbon waxes	1 - 3	8002-74-2

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### **Description of necessary first aid measures**

Description of necessary first and mea	isur	<u> </u>
Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious,



## 11000WHW WILFLEX OASIS HYDRATE WHITE

Version Number 1.5 Page 4 of 19 Revision Date 04/02/2018 Print Date 04/03/2018

place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact** : Causes skin irritation.

**Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

pain or irritation

watering

redness

**Inhalation** : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation redness

**Ingestion** : No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

**Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms

may be delayed. The exposed person may need to be kept under

medical surveillance for 48 hours.

**Specific treatments** : No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without

suitable training. It may be dangerous to the person providing aid to

give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

# **Section 5. Firefighting measures**

#### **Extinguishing media**

**Suitable extinguishing media** : In case of fire, use water spray (fog), foam, dry chemical or CO<sub>2</sub>.

**Unsuitable extinguishing media** : None known.



#### 11000WHW WILFLEX OASIS HYDRATE WHITE

Version Number 1.5 Revision Date 04/02/2018 Page 5 of 19 Print Date 04/03/2018

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon dioxide

carbon monoxide nitrogen oxides sulfur oxides metal oxide/oxides

Special protective actions for firefighters Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without

suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is

inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

See also the information in "For non-emergency personnel".

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment

if released in large quantities.

#### Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with

water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate

waste disposal container. Dispose of via a licensed waste disposal



## 11000WHW WILFLEX OASIS HYDRATE WHITE

Version Number 1.5 Revision Date 04/02/2018 Page 6 of 19 Print Date 04/03/2018

Large spill

contractor.

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

#### Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### Occupational exposure limits

Ingredient name	<b>Exposure limits</b>	
	6/19	



## 11000WHW WILFLEX OASIS HYDRATE WHITE

Version Number 1.5 Revision Date 04/02/2018 Page 7 of 19 Print Date 04/03/2018

Paraffin waxes and Hydrocarbon waxes	OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 2 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) 2 mg/m3 Form: Fume ACGIH TLV (1994-09-01) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 2 mg/m3 Form: Fume
Urea	AIHA WEEL (1999-01-01) Time Weighted Average (TWA) 10 mg/m3
1,2-Propanediol	AIHA WEEL (1999-01-01) Time Weighted Average (TWA) 10 mg/m3
Distillates (petroleum), hydrotreated light	ACGIH TLV (2003-01-01) Calculated as total hydrocarbon vapor TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 200 mg/m3
Titanium dioxide	OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 15 mg/m3 Form: Total dust NIOSH REL (1994-06-01)  ACGIH TLV (1996-05-18) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 10 mg/m3

**Appropriate engineering controls** 

Good general ventilation should be sufficient to control worker

exposure to airborne contaminants.

**Environmental exposure controls** 

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of

environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be

necessary to reduce emissions to acceptable levels.

### **Individual protection measures**

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical

products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety



## 11000WHW WILFLEX OASIS HYDRATE WHITE

Version Number 1.5 Revision Date 04/02/2018 Page 8 of 19 Print Date 04/03/2018

showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used

when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a

higher degree of protection: chemical splash goggles.

**Skin protection** 

**Hand protection**: Chemical-resistant, impervious gloves complying with an approved

standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves

cannot be accurately estimated.

**Body protection**: Personal protective equipment for the body should be selected based

on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures

should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that

meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper

fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

#### **Appearance**

**Evaporation rate** 

Physical state liquid [liquid] Color WHITE Odor Not available. **Odor threshold** Not available. Not available. pН **Melting point** Not available. **Boiling point** Not available. Flash point Not available. **Burning time** Not available. **Burning rate** 

Not available.
Not available.



## 11000WHW WILFLEX OASIS HYDRATE WHITE

Version Number 1.5 Page 9 of 19 Revision Date 04/02/2018 Print Date 04/03/2018

Flammability (solid, gas) : Not available.

Lower and upper explosive : Lower: Not available. (flammable) limits : Upper: Not available.

Vapor pressureNot available.Vapor densityNot available.Relative densityNot available.SolubilityNot available.Solubility in waterNot available.Partition coefficient: n-Not available.

octanol/water

Auto-ignition temperature: Not available.Decomposition temperature: Not available.SADT: Not available.

Viscosity : Dynamic: Not available.

**Kinematic:** Not available.

## Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or

its ingredients.

Chemical stability : Stable under recommended storage and handling conditions (see

Section 7).

**Possibility of hazardous reactions**: Under normal conditions of storage and use, hazardous reactions will

not occur.

**Conditions to avoid** : Keep away from extreme heat and oxidizing agents.

**Incompatible materials** : Keep away from strong acids.

Oxidizer.

**Hazardous decomposition**: Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

## Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Information on toxicological effects**

#### **Acute toxicity**

products

Product/ingredient name	Result	Species	Dose	Exposure
Paraffin waxes and Hydrocarb	on waxes			
	LD50 Oral	Rat	2,000 mg/kg	-
Remarks - Inhalation:	No applicable toxicity data			
Remarks - Dermal:	No applicable toxicity data			



# 11000WHW WILFLEX OASIS HYDRATE WHITE

Version Number 1.5 Revision Date 04/02/2018 Page 10 of 19 Print Date 04/03/2018

Urea							
	LD50 Oral	Rat	8,471 mg/kg	-			
Remarks - Inhalation:	No applicable toxic	No applicable toxicity data					
Remarks - Dermal:	No applicable toxic	city data					
1,2-Propanediol							
	LD50 Oral	Rat	20,000 mg/kg	-			
Remarks - Inhalation:	No applicable toxicity data						
	LD50 Dermal	Rabbit	20,800 mg/kg	-			
Distillates (petroleum), hydroti	Distillates (petroleum), hydrotreated light						
Remarks - Oral:	No applicable toxicity data						
Remarks - Inhalation:	No applicable toxic	No applicable toxicity data					
Remarks - Dermal:	No applicable toxicity data						
Titanium dioxide	Titanium dioxide						
Remarks - Oral:	No applicable toxicity data						
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h			
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-			

Conclusion/Summary : Mixture.Not fully tested.

## Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Paraffin waxes and	Skin -	Rabbit			-
Hydrocarbon waxes	Moderate				
	irritant				
	Eyes - Mild	Rabbit			-
	irritant				
	Skin - Mild	Rabbit		24 hrs	-
	irritant				
	Eyes - Mild	Rabbit		24 hrs	-
	irritant				
Urea	Skin -	Human		24 hrs	-
	Moderate				
	irritant				
	Skin - Mild	Human		72 hrs	-
	irritant				
1,2-Propanediol	Skin - Mild	Woman		96 hrs	-
	irritant				
	Skin - Mild	Human		168 hrs	-
	irritant				
	Skin -	Human		72 hrs	-
	Moderate				
	irritant				
	Eyes - Mild	Rabbit			-
	irritant				



## 11000WHW WILFLEX OASIS HYDRATE WHITE

Version Number 1.5 Revision Date 04/02/2018 Page 11 of 19 Print Date 04/03/2018

	Eyes - Mild	Rabbit	24 hrs	-
	irritant			
	Skin -	Child	96 hrs	-
	Moderate			
	irritant			
Titanium dioxide	Skin - Mild	Human	72 hrs	-
	irritant			

Conclusion/Summary

Skin: Mixture.Not fully tested.Eyes: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

**Sensitization** 

Conclusion/Summary

Skin: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

**Mutagenicity** 

**Conclusion/Summary** : Mixture.Not fully tested.

Carcinogenicity

Conclusion/Summary : Mixture. Not fully tested.

Classification

Clubbilicution			
Product/ingredient	OSHA	IARC	NTP
name			
Titanium dioxide		2B	

#### **Reproductive toxicity**

**Conclusion/Summary** : Mixture.Not fully tested.

**Teratogenicity** 

**Conclusion/Summary** : Mixture.Not fully tested.

**Specific target organ toxicity (single exposure)** 

Not available.

**Specific target organ toxicity (repeated exposure)** 

Not available.

**Aspiration hazard** 



## 11000WHW WILFLEX OASIS HYDRATE WHITE

Version Number 1.5 Page 12 of 19 Revision Date 04/02/2018 Print Date 04/03/2018

Product/ingredient name	Result
Distillates (petroleum), hydrotreated light	ASPIRATION HAZARD - Category 1

Information on likely routes of

exposure

Not available.

Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact** : Causes skin irritation.

**Ingestion** : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

pain or irritation

watering

redness

**Inhalation** : No specific data.

**Skin contact** : Adverse symptoms may include the following:

irritation

redness

**Ingestion** : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

**Potential chronic health effects** 

**Conclusion/Summary** : Mixture. Not fully tested.

General: No known significant effects or critical hazards.Carcinogenicity: No known significant effects or critical hazards.Mutagenicity: No known significant effects or critical hazards.Teratogenicity: No known significant effects or critical hazards.



## 11000WHW WILFLEX OASIS HYDRATE WHITE

Version Number 1.5 Page 13 of 19 Revision Date 04/02/2018 Print Date 04/03/2018

Developmental effects: No known significant effects or critical hazards.Fertility effects: No known significant effects or critical hazards.

## **Numerical measures of toxicity**

### **Acute toxicity estimates**

Route	ATE value
Oral	77,435.3 mg/kg
Route	ATE value
Inhalation (vapors)	85.29 mg/l

# Section 12. Ecological information

### **Toxicity**

Product/ingredient name	Result	Species	Exposure	
Paraffin waxes and Hydrocarbon waxes				
Remarks - Acute - Fish:	No applicable toxicity data			
Remarks - Acute - Aquatic	No applicable toxicity data			
invertebrates.:				
Remarks - Acute - Aquatic	No applicable toxicity data			
plants:				
Remarks - Chronic - Fish:	No applicable toxicity data			
Remarks - Chronic -	No applicable toxicity data			
Aquatic invertebrates.:				
Urea				
	Acute LC50 0.000023 Mg/l Fresh	Fish - Fish	96 h	
	water			
Remarks - Acute - Fish:	Acute			
	Acute EC50 6,573.1 Mg/l Fresh	Aquatic invertebrates.	48 h	
	water	Crustaceans		
Remarks - Acute - Aquatic	Acute			
invertebrates.:				
	Acute EC50 3,910 Mg/l Fresh	Aquatic invertebrates.	48 h	
	water	Daphnia		
Remarks - Acute - Aquatic	Acute			
invertebrates.:				
Remarks - Acute - Aquatic	No applicable toxicity data			
plants:		T-11.		
	Chronic NOEC 2,000 Mg/l Fresh	Fish - Fish	30 d	
	water			



# 11000WHW WILFLEX OASIS HYDRATE WHITE

Version Number 1.5 Revision Date 04/02/2018 Page 14 of 19 Print Date 04/03/2018

Remarks - Chronic - Fish:	Chronic			
Remarks - Chronic -				
Aquatic invertebrates.:	No applicable toxicity data	No applicable toxicity data		
1,2-Propanediol				
1,2-110panedioi	Acute LC50 710 Mg/l Fresh water	Fish - Fish	96 h	
Remarks - Acute - Fish:	Acute  Acute	1 1511 - 1 1511	70 II	
Kemarks - Acute - Fish.	Acute EC50 > 110 Mg/l Fresh	Aquatic invertebrates.	48 h	
	water	Daphnia	40 II	
Remarks - Acute - Aquatic	Acute	Бирини		
invertebrates.:	Teate			
111 ( 01 00 21 400 31	Acute LC50 1,020 Mg/l Fresh	Aquatic invertebrates.	48 h	
	water	Crustaceans	10 11	
Remarks - Acute - Aquatic	Acute	l.	-L	
invertebrates.:				
Remarks - Acute - Aquatic	No applicable toxicity data			
plants:	,			
Remarks - Chronic - Fish:	No applicable toxicity data			
Remarks - Chronic -	No applicable toxicity data			
Aquatic invertebrates.:				
Distillates (petroleum), hydroti	reated light			
	Acute LC50 2.2 Mg/l Fresh water	Fish - Fish	96 h	
Remarks - Acute - Fish:	Acute			
Remarks - Acute - Aquatic	No applicable toxicity data			
invertebrates.:				
Remarks - Acute - Aquatic	No applicable toxicity data			
plants:				
Remarks - Chronic - Fish:	No applicable toxicity data			
Remarks - Chronic -	No applicable toxicity data	No applicable toxicity data		
Aquatic invertebrates.:				
Titanium dioxide	1 000 1 000 1 1 1 1		1061	
	Acute LC50 > 1,000 Mg/l Marine	Fish - Fish	96 h	
Describe A 4 E'	water			
Remarks - Acute - Fish:	Acute Acute I C50 2 Mg/l Fresh mater	A acception in company to a	40.1	
	Acute LC50 3 Mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h	
Remarks - Acute - Aquatic	Acute	Crustaceans		
invertebrates.:	Acute			
miver tebrates	Acute LC50 6.5 Mg/l Fresh water	Aquatic invertebrates.	48 h	
	Treate Deso 6.5 Mg/11165H water	Daphnia	1011	
Remarks - Acute - Aquatic	Acute	1		
invertebrates.:				
Remarks - Acute - Aquatic	No applicable toxicity data			
plants:				
Remarks - Chronic - Fish:	No applicable toxicity data			
	, ,			



## 11000WHW WILFLEX OASIS HYDRATE WHITE

Version Number 1.5 Page 15 of 19 Revision Date 04/02/2018 Print Date 04/03/2018

Remarks - Chronic - No applicable toxicity data

Aquatic invertebrates.:
Conclusion/Summary

Not available.

Persistence and degradability

**Conclusion/Summary** : Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Urea	-1.73	-	low
1,2-Propanediol	-1.070.085	-	low

#### **Mobility in soil**

Soil/water partition coefficient

(KOC)

Not available.

Other adverse effects : No known significant effects or critical hazards.

# Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed



#### 11000WHW WILFLEX OASIS HYDRATE WHITE

Version Number 1.5 Page 16 of 19 Revision Date 04/02/2018 Print Date 04/03/2018

## **Section 14. Transport information**

U.S.DOT 49CFR

Ground/Air/Water

: Not classified as dangerous for transport purposes.

International Air ICAO/IATA

: Not classified as dangerous for transport purposes.

International Water

IMO/IMDG

: Not classified as dangerous for transport purposes.

## Section 15. Regulatory information

**U.S. Federal regulations** 

: United States - TSCA 12(b) - Chemical export notification: None

of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed

United States - TSCA 4(f) - Priority risk review: Not listed

United States - TSCA 5(a)2 - Final significant new use rules: Not

listed

United States - TSCA 5(a)2 - Proposed significant new use rules:

Not listed

United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not

determined

United States - TSCA 8(a) - Preliminary assessment report

(PAIR): Not listed

**United States - TSCA 8(c) - Significant adverse reaction (SAR):** 

Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority

pollutants: Not listed

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental



## 11000WHW WILFLEX OASIS HYDRATE WHITE

Version Number 1.5 Revision Date 04/02/2018

Page 17 of 19 Print Date 04/03/2018

release prevention - Toxic substances: Not listed

**United States - Department of commerce - Precursor chemical:** 

Not listed

Clean Air Act Section 112(b)

**Hazardous Air Pollutants (HAPs)** 

Clean Air Act Section 602 Class I

**Substances** 

Clean Air Act Section 602 Class II

**Substances** 

**DEA List I Chemicals (Precursor** 

Chemicals)

**DEA List II Chemicals (Essential** 

Chemicals)

Not listed

Not listed

Not listed

Not listed

Not listed

not applicable

US. EPA CERCLA Hazardous Substances (40 CFR 302)

SARA 311/312

Classification Immediate (acute) health hazard

#### **Composition/information on ingredients**

Name	%	Classification
Paraffin waxes and Hydrocarbon waxes	1 - 3	AH
Urea	3 - 5	AH
1,2-Propanediol	5 - 10	АН
Distillates (petroleum), hydrotreated light	10 - 25	F, AH
Titanium dioxide	10 - 25	СН

#### **SARA 313**

Not applicable.

**State regulations** 

Massachusetts None of the components are listed. None of the components are listed. **New York** The following components are listed: **New Jersey** 

Paraffin waxes and Hydrocarbon waxes

Barium sulfate



## 11000WHW WILFLEX OASIS HYDRATE WHITE

Version Number 1.5 Revision Date 04/02/2018 Page 18 of 19 Print Date 04/03/2018

1,2-Propanediol

Titanium dioxide

Pennsylvania : The following components are listed:

Titanium dioxide

1,2-Propanediol

Barium sulfate

Paraffin waxes and Hydrocarbon waxes

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

United States inventory (TSCA 8b) : All components are listed or exempted.

**Canada inventory** : Not determined.

### **International regulations**

### **Inventory list**

Australia Not determined. Canada Not determined. China Not determined. **Europe inventory** Not determined. Japan Not determined. New Zealand Not determined. **Philippines** Not determined. Republic of Korea Not determined. Taiwan Not determined. **Turkey** Not determined.

**United States** : All components are listed or exempted.

## Section 16. Other information

#### **Hazardous Material Information System (U.S.A.)**

Health	/	2
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4



## 11000WHW WILFLEX OASIS HYDRATE WHITE

Version Number 1.5 Revision Date 04/02/2018 Page 19 of 19 Print Date 04/03/2018

representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

**History** 

Date of printing: 04/03/2018Date of issue/Date of revision: 04/02/2018Date of previous issue: 06/08/2015

Version : 1.5

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From

Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

**References** : Not available.

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.